

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
21 April 2005 (21.04.2005)

PCT

(10) International Publication Number  
**WO 2005/035696 A1**

(51) International Patent Classification<sup>7</sup>: C10L 1/32

(21) International Application Number:  
PCT/KR2003/002105

(22) International Filing Date: 13 October 2003 (13.10.2003)

(25) Filing Language: Korean

(26) Publication Language: English

(71) Applicant and

(72) Inventor: KIM, Ho Kyun [KR/KR]; 102 Pungnimbilla,  
36-1 Nonhyeon1-dong, Gangnam-gu, Seoul 135-815 (KR).

(74) Agent: CHOI, Duk Kyu; 5th Floor Chunwoo Bldg., 736  
Yoksam-dong, Gangnam-gu, Seoul 135-080 (KR).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,  
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,  
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,  
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: EMULSION FUEL AND METHOD OF PREPARING THE SAME

(57) Abstract: The emulsion fuel according to the present invention is prepared by emulsifying about 55 to 90 % by weight of a mixture of heavy oil, 45 to 10 % by weight of water, and 0.3 to 0.8 % by weight of a catalyst. The catalyst comprises caustic soda (sodium hydroxide) and calcium dichloride in half and half. The calcium chloride can be partly substituted with calcium sulfate.



WO 2005/035696 A1